

NX I-deas Material Data Catalog

Benefits

- Gain easy access to mechanical and materials property data for engineering and analysis
- Get all the reference data you need for material properties from a single source
- Rely on current industry-standard data sources and governmental approval to ensure your material specs are up to code

Features

- Materials data library for analysis (MDLA) covers thermoplastics, thermosets, elastomers, ceramics, composites, metals, wood and glass
- The MIL5 library covers materials commonly used for aerospace applications, including steel, stainless steel, aluminum, magnesium, titanium, heat resistant alloys and special purpose alloys
- The Metals library covers aluminum, copper, steel, stainless steel, nickel and reactive alloys

Summary

NX™ I-deas™ Material Data Catalog software is a set of three independent add-on modules within NX I-deas software that is accessible via the Material Data System. To display the catalog entries you must have a license for one of these NX I-deas packages: NX I-deas Digital Product Design suite, NX I-deas MasterFEM, Artisan, or Master Modeler. Material Data Catalog consists of three libraries – materials data library for analysts, MIL5 library and Metals library – which enable you to access a wealth of information and references on materials and metals properties and manufacturers. Easy to use and aided by robust graphics, Material Data Catalog is a must for those using NX I-deas for engineering and analysis.


Linking master models to materials and metals properties

The Material Data Catalog enables users to link master models to materials and metals properties via three independent, add-on library modules: MDLA, MIL5 and Metals.

MDLA

Materials data library for analysts (MDLA) consists of more than 450 records covering thermoplastics, thermosets, elastomers, ceramics, composites, metals, wood and glass. The MDLA was developed and is maintained using the following data sources:

- Manufacturer's technical manuals and data sheets
- Direct contact with manufacturer's technical personnel
- In-house synthesis/interpolation techniques
- Recognized textbook sources
- Trade magazines



NX

www.siemens.com/nx

SIEMENS

NX I-deas Material Data Catalog

Features *continued*

- For MIL5 and Metals you can access graphs of material characteristics, including stress versus strain at various temperatures and specific heat versus temperature

System requirements

Material Data Catalog shares the NX I-deas system requirements.

Recommended system configuration

For information on particular operating systems or graphics cards, please visit <http://support.ugs.com/>

Nominal properties and property ranges are provided for all MDLA materials. Temperature-dependent data, when available, is provided. The library references specific manufacturers.

MIL5 aerospace materials library

The MIL5 library consists of more than 1,370 records covering materials commonly used for aerospace applications, including steel, stainless steel, aluminum, magnesium, titanium, heat resistant alloys and special purpose alloys. MIL5 is compiled and updated on a regular basis using the U.S. Government MIL-HDBK-5. The data has been approved for use by all departments and agencies of the U.S. Department of Defense and Federal Aviation Administration.

Graphs of material characteristics include:

- Maximum stress versus fatigue life
- Room temperature strength versus temperature

- Thermal expansion versus temperature
- Specific heat versus temperature
- Thermal conductivity versus temperature
- Stress versus strain at various temperatures

Statistical A-, B- and S-basis property values are provided for all materials. MIL5 also provides references to specific thicknesses, tempers, test temperatures and test conditions.

Metal materials library

The Metals library consists of more than 2,640 records covering aluminum, copper, steel, stainless steel, nickel and reactive alloys. The records were compiled and are updated from manufacturer data sheets and industry-standard sources. The data

should be used for initial design analysis only and should not be considered design-allowable information.

Graphs of metal characteristics include:

- Strength versus temperature
- Coefficient of thermal expansion versus temperature
- Specific heat versus temperature
- Thermal conductivity versus temperature
- Stress versus strain at various temperatures

The Metals library refers to specific trade names and UNS designations, and, also, the library provides references to thicknesses, tempers, test temperatures and test conditions.

Material properties data for engineering and analysis

| MDLA | MIL5 | Metals |
|----------------------------------|----------------------------------|----------------------------------|
| Young's modulus | Young's modulus | Young's modulus |
| Shear modulus | Shear modulus | Shear modulus |
| Poisson's ratio | Poisson's ratio | Poisson's ratio |
| Yield strength | Yield strength | Yield strength |
| Ultimate strength | Ultimate strength | Ultimate strength |
| Elongation | Elongation | Elongation |
| Density | Density | Density |
| Coefficient of thermal expansion | Coefficient of thermal expansion | Coefficient of thermal expansion |
| Thermal conductivity | Thermal conductivity | Thermal conductivity |
| Specific heat | Specific heat | Specific heat |
| | Material thickness | |
| | Ultimate bearing stress | |
| | Ultimate shear stress | |
| | Yield bearing stress | |
| | Yield compressive stress | |

Contact

Siemens PLM Software

Americas 800 498 5351

Europe 44 (0) 1276 702000

Asia-Pacific 852 2230 3333

www.siemens.com/nx

© 2011 Siemens Product Lifecycle Management Software Inc. All rights reserved. Siemens and the Siemens logo are registered trademarks of Siemens AG. D-Cubed, Femap, Geolus, GO PLM, I-deas, Insight, JT, NX, Parasolid, Solid Edge, Teamcenter, Tecnomatix and Velocity Series are trademarks or registered trademarks of Siemens Product Lifecycle Management Software Inc. or its subsidiaries in the United States and in other countries. All other logos, trademarks, registered trademarks or service marks used herein are the property of their respective holders.
X3 2401 2/11 B