

NX CAE environment for LS-Dyna solver

Accelerating pre- and postprocessing for crash analysis

Benefits

- Enables engineers using NX CAE to generate finite element models for the LS-Dyna solver
- Simplifies the LS-Dyna modeling process by enabling engineers to create analysis models based on geometry
- Reduces or eliminates intermediate manual processing of data files by generating run-ready decks directly from NX CAE
- Immerses engineers in the LS-Dyna environment by using familiar LS-Dyna terminology and extensive support of LS-Dyna-specific elements and entities

Summary

The LS-Dyna environment for NX[™] CAE enables engineers to build finite element models and define solution parameters for the LS-Dyna solver. The environment immerses engineers with familiar LS-Dyna language for element definitions, loads and boundary conditions, solution parameters and other common LS-Dyna nomenclature. In addition to model definition capabilities, the LS-Dyna environment enables bi-directional import/export capabilities that enable you to import current or legacy LS-Dyna data files and results, as well as export runready LS-Dyna input data files.

Using NX to create LS-Dyna models The power of NX CAE pre/postprocessing is an ideal partner for creating LS-Dyna models and solutions. NX CAE simplifies the modeling process by integrating high-end analyst modeling tools with world-class geometry capabilities that assist you with developing analysis models faster than with traditional CAE preprocessors. Adding the LS-Dyna environment to NX CAE enables you to build LS-Dyna run-ready input data files, so little or no intermediate processing is ever needed. In addition to building LS-Dyna models, the NX LS-Dyna environment imports solution results directly from LS-Dyna *.d3p results files into NX for postprocessing. The environment delivers import/export capabilities so you can import LS-Dyna data decks into NX for modification and then export runready decks for solution.



Dataset courtesy of the National Crash Analysis Center at George Washington University.

NX CAE environment for LS-Dyna solver

Elements and other entities

A wide variety of elements and other model entities are supported.

OD elements

- Element mass: Structural mass element
- Element inertia: Lumped inertia element assigned to a node

1D elements

- Element beam: Two-node 1D linear beam element (beam, truss)
- Element beam offset: Section properties (created automatically when you define offset and use default orientation)
- Element beam orientation: Section properties (created automatically when you define orientation but not offset)
- Element beam offset orientation: Section properties (created automatically when you define both orientation and offset)
- Element discrete: Two-node 1D element (spring, damper)





............

2D elements

- Element shell (3), (4), (6), (8): Three, four, six and eight node 2D thin-shell elements
- Element shell thickness: Thickness extracted from midsurface (created automatically)
- Element shell offset: Thickness offset (created automatically when you define offset)
- Element shell beta: Material orientation (created automatically when you define the angle in element associated data)
- Element shell MCID: Material orientation (created automatically when you define material coordinate system in element associated data)
- Part composite keyword is supported in NX Laminate Composites

3D elements

- Element tshell (6), (8): Six-node and eight-node 3D solid Hex6 and Hex8 elements
- Element solid (4), (6), (8), (10): Four, six, eight and ten node 3D solid elements for isotropic materials

0. A at b*				□ ? \$ / 1
34 ×	LS-DYNA elements			
Instantial Disubles	Oursian How To Datum Related Sector			
Integrals PEX and Sociation Para				
as Varapried	Physical properties and element attributes			
anerar Dajabiliter Annathy Haddatlar Annat	The following table fors the LE-DMIA viewests that are supported in Advanced Simulation. It also, fors the Keyword and physical proper- tables that can be addeed for each element gate. For more information accus defining physical and manning properties, see <u>Physical</u> manufacture information additional accession.			
Energy information Encounted memory and properties Information contents	In the LS DYNA FEXT, you devote the restor's physical and realistic properties using the physical property named PART and the rest objects named SECTION and INCOMPLASS			
Batwitti serena Batz-batwein	For example, in a physical property dialog has such as FMRE, you can specify an IVI material or type the ID of an external US DYNA material			
Distantia and face, bit Stational Systems	You can define the material primition for 20 and 30 evenems in the physical properties, Meak Associated Data during loss, or the Element Associated Data during loss:			
Distance private the second to Disconsecurity of the second second Distance second	The following table tors the ES-DY1A elements supported in Advanced Elevication. It also lists the trajevoid and physical property tables can be defined for each element type. The SECIDON modeling stippic contents additional physical properties such as shell thereares, so constant, and as on.			
Constantia and	For descriptions of an element type, see the LS-D	VNA documentation		
Citizense Citizense	Elementi S.20194 Keywood	Description	Heah collector Physical property sprate	Bindeling object resear
C Bestey	The second second		100000	
Division of the United and Value Destrong St.	10 alternation			
Entrent-max for NX, Epicx Systems, Therman Entrent cardons	ELEVENT_NAME	60 structural mass alignment		
Etherus metrig Etherus metrig	ELEMENT_NERTA	Longed mette element anoigned to a roote		
and the second sec	10 stanards			
annery Abdraction	a statut beau	Survey of Second Second	And Annual	Discourse and the
eservice PDIs	ELEVEN (DOWN	element (beam, trust)	Provi granit	HURGLASS
Contex Contexe	ELEMENT_BEAU_COTTRET	Sector properties (created	Polit (search)	BECTON_BEAM
initial and inset faults		define offset and use pales/h		HOURGLASS
tring the Madel	ELEMENT_REAH_ORENTATION	Saction properties (created	PART (heart)	SECTON, BEAM
digtra Arabas Inggran Soulator		Automatically often you define orientation but not offset;		HOURGLADS
a series	IL RANGE BRACK CONTRACT COMPLETATION	Realized second as loss and	Ridt Annul	Sectors Bears

• Element solid ortho: Material orientation for orthotropic/anisotropic materials (created automaticaly when you define material orientation). Material orientation is defined by two vectors

Boundary conditions

- Surface-to-surface contact
- Single point constraint
- Constrained node set
- Rigid wall definition
- Initial velocity

Note:

A complete list of LS-Dyna export entity support is provided in the NX online help documentation under the following header: Advanced Simulation/Solving the Model/Importing and Exporting Model Data/.

Compatibility

The LS-Dyna environment is compatible with the following LS-Dyna releases:

LS-Dyna v971R6.0 or earlier



Supported hardware/OS

The LS-Dyna environment is an add-on module within the NX CAE product suite. It requires a license of NX CAE as a prerequisite. It is available on all NX supported hardware/OS platforms (Windows and Linux) including selected 64-bit platforms.

Contact

iemens PLM Software mericas +1 314 264 8499 urope +44 (0) 1276 41320(sia-Pacific +852 2230 3308

www.siemens.com/plm

© 2014 Siemens Product Lifecycle Management Software Inc. Siemens and the Siemens logo are registered trademarks of Siemens AG. D-Cubed, Femap, Fibersim, Geolus, GO PLM, I-deas, JT, NX, Parasolid, Solid Edge, Syncrofit, Teamcenter and Tecnomatix are trademarks or registered trademarks of Siemens Product Lifecycle Management Software Inc. or its subsidiaries in the United States and in other countries. All other logos, trademarks, registered trademarks or service marks belong to their respective holders. 14735-Y4 12/14 B